Claim 1. (Previously presented)

An optical head device comprising:

an objective lens for bringing light emitted from a light source into focus on an

information recording medium;

a lens holder for holding said objective lens, said lens holder having a bearing hole

formed along a direction parallel to an optical axis of said objective lens, the bearing hole having

a diameter that gradually increases while approaching the bearing hole's openings from the

bearing hole's center;

a support shaft inserted in said bearing hole;

a light detector for receiving said light reflected from said information recording medium

and outputting information about inclination of said objective lens relative to said information

recording medium on the basis of said light received; and

an inclination drive unit for, according to said information about said inclination, turning

said lens holder on a first axis perpendicular to said support shaft.

Claim 2. (Previously presented)

The optical head device according to claim 1, wherein

said bearing hole has a wall that is generally circularly arcuate in cross-sectional shape.

2

Claim 3. (Original)

The optical head device according to claim 2, wherein

an equation (A-B)-L x tan  $\theta$  is generally satisfied, where A is a hole diameter of said

bearing hole in the vicinity of said opening, B is a hole diameter of said bearing hole in the

vicinity of said center, L is a length of said bearing hole along said optical axis of said objective

lens, and  $\theta$  is a maximum amount of correction on the turning of said lens holder.

Claim 4. (Original)

The optical head device according to claim 3, wherein

said (A-B) equals approximately to 88  $\mu m$  and said L equals approximately to 5 mm.

Claim 5. (Previously presented)

The optical head device according to claim 1,

wherein said inclination drive unit includes:

electromagnetic drive means comprising a first element mounted on said lens holder on a

second axis perpendicular to both said support shaft and said first axis perpendicular to said

support shaft, and a second element located opposite said first element; and

a magnetic material fixedly mounted on said lens holder in close vicinity to said second

element of said electromagnetic drive means.

3

DRA/CJB/kpc

Docket No.: 2257-0202P

Reply to Office Action of October 25, 2006

Docket No.: 2257-0202P

Claim 6. (Original)

The optical head device according to claim 1, further comprising:

a fluid provided in said bearing hole.

Claim 7. (Original)

The optical head device according to claim 6, wherein

said fluid includes a magnetic fluid.

Claim 8. (Original)

The optical head device according to claim 7, wherein

said lens holder further includes a permanent magnet located opposite said bearing hole

and said magnetic fluid.

Claim 9. (Previously presented)

An optical head device comprising:

an objective lens for bringing light emitted from a light source into focus on an

information recording medium;

4

DRA/CJB/kpc

Docket No.: 2257-0202P

Amendment dated February 20, 2007

Application No. 10/021,000

Reply to Office Action of October 25, 2006

a lens holder for holding said objective lens, said lens holder having a bearing hole

formed along a direction parallel to an optical axis of said objective lens, the bearing hole having

a diameter that gradually increases while approaching the bearing hole's openings from the

bearing hole's center;

a support shaft inserted in said bearing hole; and

a fluid provided in said bearing hole.

Claim 10. (Original)

The optical head device according to claim 9, wherein

said fluid includes a magnetic fluid.

Claim 11. (Original)

The optical head device according to claim 10, wherein

said lens holder further includes a permanent magnet located opposite said bearing hole

and said magnetic fluid.

Claims 12-19 (Canceled)

5

DRA/CJB/kpc